

**Mag One™**  
by Motorola

**BPR™ 40**




Introducing the  
**BPR™ 40** two-way  
portable radio!



**It's a little radio with a big list of features:**

- 8 channels for complete communication to a wide group
- 2 Programmable buttons for easy use and versatility
- High/Low power provides flexibility for a variety of situations
- Complete assortment of accessories increases radio versatility
- Backed by Motorola service and a one-year limited warranty\*
- Small size and light weight make it ideal for any business
- 12 programmable features to choose from
- Attractive price that everyone can afford

\* 6 month limited warranty on accessories



**SPECTRUM**  
COMMUNICATIONS



**MOTOROLA**

Authorized Dealer & Service Center

**Spectrum  
Communications**

[www.spectrum-communications.ca](http://www.spectrum-communications.ca)



# BPR™ 40 Portable Two-Way Radio Specifications

GENERAL SPECIFICATIONS	VHF 150-174 MHz	UHF 450-470 MHz
Channel Capacity	8	8
Model Numbers (NiMH)	AAH84KDS8AA1_N	AAH84RCS8AA1_N
Model Numbers (Li-ion)	AAH84KDS8AA2_N	AAH84RCS8AA2_N
FCC Designation	AZ489FT3810	AZ489FT4873
FCC Emissions Designators	11K0F3E/16K0F3E	11K0F3E/16K0F3E
Dimensions (H x W x L)	4.21" x 2.28" x 1.46" (107 x 58 x 37 mm)	
Weight (with NiMH/Li-ion)	11.08 ounces (314 g)/9.52 ounces (270 g)	
<b>Average Battery Life @ 5-5-90 Duty Cycle<sup>1</sup></b>		
High Power (5W/4W)	Up to 8 hours	
Low Power (1W)	Up to 11 hours	

TRANSMITTER	VHF	UHF
Frequency Range	150-174 MHz	450-470 MHz
Channel Spacing	12.5/25 kHz	12.5/25 kHz
RF Output	1 to 5W	1 to 4W
Frequency Stability <sup>2</sup>	±2.5 ppm	±2.5 ppm
Spurs and Harmonics	-63 dBc (-26 Bm)	-63 dBc (-27 Bm)
Frequency Stability <sup>2</sup>	±2.5 ppm	±2.5 ppm
FM Hum & Noise Radio <sup>2</sup> (12.5/25 kHz)	40 dB	40 dB
Modulation Limiting <sup>2</sup> (12.5/25 kHz)	±2.5 kHz / ±5 kHz	±2.5 kHz / ±5 kHz
Audio Response (0.3-3 kHz) <sup>2</sup>	+1 to -3 dB	+1 to -3 dB
Audio Distortion <sup>2</sup>	5%	5%

RECEIVER	VHF	UHF
Frequency Range	150-174 MHz	450-470 MHz
Channel Spacing	12.5/25 kHz	12.5/25 kHz
Sensitivity <sup>2</sup> (12 dB SINAD)	<-119 dBm (.25uV)	-117.5 dBm (.3uV)
Adjacent Channel Selectivity <sup>2</sup> (12.5/25 kHz)	-60 dB / -65 dB	-60 dB / -65 dB
Intermodulation <sup>2</sup> (12.5/25 kHz)	-60 dB / -65 dB	-60 dB / -65 dB
Spurious Rejection <sup>2</sup>	65 dB	65 dB
Audio Distortion <sup>2</sup>	<5%	<5%
Hum & Noise Radio <sup>2</sup> (12.5/25 kHz)	40 dB	40 dB
Conducted Emission	-57 dBm	-57 dBm
Audio Output @ <5% Distortion <sup>2</sup>	500 mW (at 8 ohm)	500 mW (at 8 ohm)

MILITARY STANDARDS 810 C, D, E and F								
	810 C		810 D		810 E		810 F	
	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
High Temperature	501.1	1	501.2	1	501.3	1	501.4	1
Low Temperature	502.1	1	502.2	1, 2	502.3	1, 2	502.4	1, 2
Temperature Shock	503.1	1	503.2	1	503.3	1	503.4	1
Solar Radiation	505.1	1	505.2	1	505.3	1	505.4	1
Humidity	507.1	2	507.2	2, 3	507.3	2, 3	507.4	3
Salt Fog	509.1	1	509.2	1	509.3	1	509.4	1
Dust	510.1	1	510.2	1	510.3	1	510.4	1
Vibration	514.2	8, 10	514.3	1	514.4	1	514.5	1

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-30°C to +60°C (Radio Only)
Sealing	Passes rain testing per IPX4
Shock & Vibration	Die-cast with impact resistance polycarbonate housing, passes EIA 603B
Dust & Humidity	Weather-resistant housing passes EIA 603B

<sup>1</sup> 5% receive, 5% transmit, 90% standby.

<sup>2</sup> All electrical specifications and methods refer to EIA/TIA 603 standards. Specifications shown are typical and subject to change without notice.

Motorola and Mag One by Motorola are registered in the U.S. Patent and Trademark Office.

All other products or service names are the property of their respective owners. © Motorola Inc. 2007.