



MOTOTRBO™

XPR™ 8300 Repeater



Supports **two simultaneous voice or data paths** in digital Time-Division Multiple-Access (TDMA) mode

100% continuous full duty cycle at 40W/UHF and 45W/VHF

Integrated power supply

Operates in **analog or digital** mode—bright, clear, colored LEDs indicate mode

LEDs clearly indicate **transmit and receive modes** in both channel slots

Rack or wall-mountable; desktop housing also available

Sturdy handles make installation and handling easier

Automated battery back-up (battery sold separately)

The MOTOTRBO system is backed by a **two-year Standard Warranty**

Doubles the number of users you can have on a single licensed 12.5 kHz channel

Integrates voice and data to increase operational efficiency

Supports integrated applications including MOTOTRBO Text Messaging Services and GPS capability for use with third-party location-tracking applications

MOTOTRBO is a **complete two-way radio system** that includes portable and mobile radios, repeaters, accessories and applications

Accelerate performance.

The next-generation professional two-way radio communications solution is here, with more performance, productivity and value—thanks to digital technology that delivers increased capacity and spectrum efficiency, integrated data communications and enhanced voice communications.

MOTOTRBO offers you a private, standards-based, cost-effective solution that can be tailored to meet your unique coverage and feature needs. This versatile portfolio provides a complete system of portable radios, mobile radios, repeaters, accessories and data applications.

General Specifications

	XPR 8300		
	VHF	UHF Band I	UHF Band II
Channel Capacity	1		
Technical RF Output	1-25 W 25-45 W	1-25 W 25-40 W	— 1-40 W
Frequency	136-174 MHz	403-470 MHz	450-512 MHz
Dimensions (HxWxL)	5.22 x 19 x 11.67 in (132.6 x 482.6 x 296.5 mm)		
Weight	31 lbs (14 kg)		
Voltage Requirements	100-240 V AC (13.6 V DC)		
Current Drain During Standby: Low Power High Power	1 A (1 A DC typical) 1 A (1 A DC typical)		
Current Drain During Transmit: Low Power High Power	3 A (75 A DC typical) 4 A (12 A DC typical)		
Operating Temperature Range	-30°C to +60°C		
Max Duty Cycle	100%		
FCC Description	1-25 W: ABZ99FT3026 25-45 W: ABZ99FT3025	1-25 W: ABZ99FT4026 25-40 W: ABZ99FT4025	1-40 W: ABZ99FT4027
IC Description	1-25 W: 109AB-99FT3026 25-45 W: 109AB-99FT3025	1-25 W: 109AB-99FT4026 25-40 W: 109AB-99FT4025	1-40 W: 109AB-99FT4027

Receiver

	XPR 8300		
	VHF	UHF Band I	UHF Band II
Frequencies	136-174 MHz	403-470 MHz	450-512 MHz
Channel Spacing	12.5 kHz / 25 kHz		
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm		
Analog Sensitivity (12 dB SINAD)	0.30 uV 0.22 uV (typical)		
Digital Sensitivity	5% BER: 0.3 uV		
Intermodulation (TIA603C)	78 dB	75 dB	
Adjacent Channel Selectivity: TIA603 TIA603C	65 dB @ 12.5 kHz, 80 dB @ 25 kHz 50 dB @ 12.5 kHz, 80 dB @ 25 kHz	65 dB @ 12.5 kHz, 75 dB @ 25 kHz 50 dB @ 12.5 kHz, 75 dB @ 25 kHz	
Spurious Rejection	80 dB	75 dB	
Audio Distortion @ Rated Audio	3% (typical)		
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz		
Audio Response	TIA603C		
Conducted Spurious Emission	-57 dBm		

Transmitter

	XPR 8300		
	VHF	UHF Band I	UHF Band II
Frequencies	136-174 MHz	403-470 MHz	450-512 MHz
Channel Spacing	12.5 kHz / 25 kHz		
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm		
Power Output: Low Power High Power	1-25 W 25-45 W	1-25 W 25-40 W	— 1-40 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz		
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz		
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz		
Adjacent Channel Power (TIA603C)	60 dB @ 12.5 kHz 70 dB @ 25 kHz		
Audio Response	TIA603C		
Audio Distortion	3%		
FM Modulation	12.5 kHz: 11K0F3E 25 kHz: 16K0F3E		
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE		
Digital Vocoder Type	AMBE+2™		
Digital Protocol	ETSI TS 102 361-1, -2, -3		

Spectrum Communications

www.spectrum-communications.ca



MOTOROLA
Authorized Dealer & Service Center

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements. Version 7 07/08

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their registered owners. © Motorola, Inc. 2008
MD-EU/TRBO/REPEATER